

COMPARE THE RELAY® FAMILY



	Relay G90 System	Relay G55 System	Relay G50 System	Relay G30 System	Relay G10S System	Relay G10 System
Stock Transmitter	TBP12			TBP06	G10TII	
Number Of Channels	14 Manual	12 Manual		6 Manual	11 Manual, 14 Automatic	14 Automatic
Line Of Sight Range (ft/m)	300/100		200/60	100/30	130/40	50/15
Frequency Response	10Hz-20kHz					
Dynamic Range	118 dB	117 dB		118 dB	110dB	
Outputs	XLR, 1/4" Main, 1/4" Tuner/Aux	XLR, 1/4"	1/4" Main, 1/4" Tuner/Aux	1/4" Main	1/4" Main, XLR Main	
Receiver Enclosure	Metal			Polycarbonate	Metal	Polycarbonate
Antenna Connection: Type	BNC: 1/2 wave		BNC: 1/4 wave	Internal		
Battery Type	(2) AA				Rechargeable	
Power	IEC	DC1G				MicroUSB
Product Height (in/mm)	1.75/44			1.25/32	3.4/87	2.6/66
Product Width (in/mm)	19/482.6	8.5/216	3.5/89	3.15/80	4.91/124.8	3.9/99
Product Depth (in/mm)	8/203		5.25/133	4.5/114	1.968/50	3.9/99
Product Weight (lb/kg)	5.20/2.4	2.2/1	.55/.3	.10/.05	.88/.4	0.65/.3

	TBP12 Transmitter	TBP06 Transmitter	G10TII Transmitter
Connector	TA4f	1/4" Unbalanced	1/4" Unbalanced plug
Controls	Power on/off, Channel select		n/a
LED Display	Power, Audio status		Power, status
Average Battery Life	8-10 hours	8 hours	7 hours (170 standby)